

Lead2Passed



Lead2Passed

HOME

ALL VENDORS

★ GUARANTEE

? FAQ

TESTIMONIALS

Login / Register My Shopcart (1)

Input your exam code ...



Try before you buy

Download a free sample of any of our exam questions and answers

- ✓ Online Test Engine: Online Tool, Convenient, easy to study. Instant Online Access. Supports All Web Browsers.
- ✓ PDF format: Easy to read and print learning materials, our products are available in PDF file format.
- ✓ Desktop Test Engine: Installable Software Application. Simulates Real Exam Environment. Practice Offline Anytime.



Security & Privacy

We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.



365 Days Free Updates

Free update is available within 365 days after your purchase. After 365 days, you will get 50% discounts for updating.



Money Back Guarantee

Full refund if you fail the corresponding exam in 60 days after purchasing. And Free get any another product.



Instant Download

After Payment, our system will send you the products you purchase in mailbox in a minute after payment. If not received within 2 hours, please contact us.

<http://www.lead2passed.com>

Valid Certification Exam Dumps Materials and Study Guide -
Lead2Passed

Exam : **132-S-900-7**

Title : Avaya IP Telephony Design
Elective Exam

Vendor : Avaya

Version : DEMO

NO.1 A client is implementing an S87xx Media Server with several G650 Media Gateways. y are concerned with overheating in the equipment room, especially in the equipment power units. Which two conditions cause a G650 power supply to initiate an emergency shutdown? (Choose two.)

- A. overvoltage
- B. overheating
- C. undervoltage
- D. high humidity

Answer: A,B

NO.2 Within an S8500 Server, 25 IP telephony endpoints are simultaneously connected to 10 digital sets, 10 IP sets, and 5 CO trunks.

How many DSPs are in use if G.711 is incorporated?

- A. 15
- B. 25
- C. 30
- D. 50

Answer: A

NO.3 The customer plans to add remote IP users when they implement VoIP on their network.

What information about the customer's data network do you need to know to verify that remote users can be supported? (Choose three.)

- A. codec administration
- B. network region for each remote user
- C. applications the remote user will be using
- D. bandwidth the remote user will have access to
- E. the average round trip between the VPN users and the voice network

Answer: C,D,E

NO.4 You are developing IP Telephony bandwidth requirements for WAN traffic between two S87xx sites. The client estimates that simultaneous non-IP Telephony traffic will occupy 1.5 Mbps. In addition, they estimate that using G.729, 55 simultaneous IP calls need to be provided access to the WAN link.

What estimated bandwidth will the IP Telephony traffic add to the WAN traffic?

- A. 1.5 Mbps
- B. 275 Kbps
- C. 1650 Kbps
- D. 4675 Kbps

Answer: C

NO.5 Which two recommendations of a network assessment allow Avaya IP phones to boot up properly with dynamic addressing? (Choose two.)

- A. DHCP Site Specific Option 167 being set up correctly
- B. DHCP Site Specific Option 176 being set up correctly
- C. using Fast Spanning Tree Protocol (FSTP) at the port level

D. turning off Spanning Tree Protocol (STP) at the switch level

Answer: B,C

NO.6 Your client is planning to implement IP Telephony on their recently installed S8500. They will have local IP sets and IP connected remote users (IP Softphone). In addition, they need connectivity to a limited-bandwidth WAN between headquarters and their manufacturing plant. The client is interested in setting up network regions.

What are three reasons to consider network regions in your overall design? (Choose three.)

- A. to associate parameters such as codecs and locations to groups of IP endpoints
- B. to provide IP endpoints certain mandatory use of resources that belong in the same region as the endpoint
- C. to provide IP endpoints certain preference to use resources that belong in the same region as the endpoint
- D. to associate IP endpoints with a type of signaling resource (CLANS) to load balance registration among the CLANS in multiple regions
- E. to associate IP endpoints with a type of signaling resource (CLANS) to load balance registration among the CLANS in the same region

Answer: A,C,E

NO.7 Which of the following does a typical Cisco design include?

- A. Right to Use for Call Manager
- B. Right to Use for Growth
- C. Right to Use for Phones
- D. Right to Use for Redundancy

Answer: C

NO.8 An Avaya customer with a large contact center is IP enabling their S87xx and will allow 25 users to work from home via IP Agent in the Telecommuter mode.

What is the minimum hardware required in the S87xx to provide this application?

- A. one CLAN board only
- B. one Media Processor board only
- C. one CLAN and one Media Processor board
- D. no hardware is required, only software.

Answer: A

NO.9 What needs to be considered at an Enterprise Survivability Server (ESS) location when implementing an agent recording solution?

- A. H.323 trunks
- B. locally sourced announcements
- C. Application Enablement Services (AES)
- D. Separation of Bearer and Signaling (SBS)

Answer: C

NO.10 A customer has two sites connected over a 512k serial WAN link. There are 40 employees at

the main site and 20 employees at the remote site. Since the server bank and all trunks terminate at the main location, the customer has concerns about the bandwidth over the WAN link. They request a network assessment.

Which two design considerations are pertinent to the bandwidth on the WAN link? (Choose two.)

- A. VLAN capable Ethernet switch
- B. telecommuters using IP Softphone to access network resources
- C. number of voice calls going through the WAN link during peak time
- D. graphic-based programs used on the network between the two sites

Answer: C,D